



SPRING-LOADED WHEELED AMPERAGE CONTROL

- Returns to off automatically
- Insures electrode not "hot" when not in use
- Great for tack welding, short or long welds, and "bumping" technique
- Spring included with installation instructions
- Can be positioned closer to torch head for optimum torch control

Remote amperage controls provide welding machine contactor on-off, activate gas and/or water solenoids, and provide full range current output control. Handle style includes Velcro® straps where one size fits all handle diameters and retrofits easily on all makes of TIG torches.

Spring-loaded wheel (optional)

Fully enclosed housing, protects potentiometer

Metal shielded cable protects against high frequency

Velcro® straps secure control to the handle



SPRING-LOADED WHEELED AMPERAGE CONTROL REPLACEMENT PARTS

**OTHER
AMPERAGE
CONTROLS
OFFERED
BY CK**



ROTARY AMPERAGE CONTROL

*Replace foot pedal
amperage controls
with fingertip operated
amperage controls,
available as a complete
handle assembly.*




LINEAR AMPERAGE CONTROL

*Linear slide actuator
for complete on/off
and full amperage
control. Protected
against high frequency.*

MACHINE MAKE POTENTIOMETER RATING	AMPERAGE CONTROL TYPE	PLUG CONFIGURATION & PIN COUNT	CONTROL CABLE LENGTH	VELCRO™ STRAPS
				ONE SIZE FITS ALL
LINCOLN ELECTRIC 10K Ohm	Wheel	5 Pin Plug	15 ft. (4.6 m)	WACCV-10-1-L5
			28 ft. (8.5 m)	WACCV-10-2-L5
			53 ft. (16.2 m)	WACCV-10-3-L5
		6 Pin Plug	15 ft. (4.6 m)	WACCV-10-1-L6
			28 ft. (8.5 m)	WACCV-10-2-L6
			53 ft. (16.2 m)	WACCV-10-3-L6
MILLER ELECTRIC 1K Ohm	Wheel	14 Pin Plug	15 ft. (4.6 m)	WACCV-1-1-M14
			28 ft. (8.5 m)	WACCV-1-2-M14
			53 ft. (16.2 m)	WACCV-1-3-M14
		5 Pin Plug	15 ft. (4.6 m)	WACCV-1-1-M5
			28 ft. (8.5 m)	WACCV-1-2-M5
			53 ft. (16.2 m)	WACCV-1-3-M5
THERMAL DYNAMICS 5K Ohm	Wheel	14 Pin Plug	15 ft. (4.6 m)	WACCV-5-1-TD14
			28 ft. (8.5 m)	WACCV-5-2-TD14
			53 ft. (16.2 m)	WACCV-5-3-TD14
		8 Pin Plug	15 ft. (4.6 m)	WACCV-5-1-TD8
			28 ft. (8.5 m)	WACCV-5-2-TD8
			53 ft. (16.2 m)	WACCV-5-3-TD8

EXPLODED VIEW



AMPHENOL PLUGS

OTHER MODELS AVAILABLE

6P (SPECIFY MACHINE)
(i.e. 6P-M14-M FOR MILLER 14 PIN PLUG)



MACHINE AND PLUG CONFIGURATION	PLUG TYPE
MILLER 14 PIN PLUG	6P-M14-M
LINCOLN 6 PIN PLUG	6P-L6-M
THERMAL 8 PIN PLUG	6P-TD8-M

CK Worldwide Inc., PO Box 1636, Auburn, WA 98071 USA
Phone: 1.800.426.0877 Fax: 1.800.327.5038

www.CKWORLDWIDE.com
FORM420