

MAGNUM[®] PRO WATER-COOLED WELDING GUNS

IMPROVING COMFORT AND PERFORMANCE



KEY FEATURES

The Magnum[®] PRO Water-Cooled Welding Guns are built to tackle high-heat applications while maintaining operator comfort.

- **100% Duty Cycle** – The 400A and 500A guns run at 100% duty cycle using 90/10 mixed gas, making them ideal for high heat applications.
- **Premium Tip Performance** – The large diameter and mass of the Magnum PRO Copper Plus™ contact tips help disperse heat and keep the tips cooler, expanding their life.
- **Expendables Built for High Heat** – The 500A water-cooled gooseneck design keeps the nozzle cool in high-heat applications.
- **Over-Molded Handle Design** – The soft rubber over molding enhances comfort and allows for an easier grip of the gun.

Processes »

MIG, Pulsed MIG, FCAW

Output »



Input »



Product Number »

See product specifications table for details

What's Included »

- » 60° Gun Tube – KP4527-60 (400A Guns), KP4526-60 (500A Guns)
- » Diffuser – KP4380-1
- » 0.045 in. Contact Tip – KP2745-045
- » 1/8 in. Recessed, 5/8 in. ID Nozzle – KP4523-1-62R
- » 0.035-0.045 in., 15 ft. Liner – KP44-3545-15

EXPENDABLE PARTS

CONTACT TIPS, 550A

Wire Diameter, in. (mm)	Standard, qty. 10	Standard, qty. 100	Extended Life, qty. 10	Extended Life, qty. 100
0.035 (0.9)	KP2745-035	KP2745-035-B100	KP2745-035R	KP2745-035R-B100
0.040 (1.0)	KP2745-040	KP2745-040-B100	KP2745-040R	KP2745-040R-B100
0.045 (1.2)	KP2745-045	KP2745-045-B100	KP2745-045R	KP2745-045R-B100
0.052 (1.3)	KP2745-052	KP2745-052-B100	KP2745-052R	KP2745-052R-B100
1/16 (1.6)	KP2745-116	KP2745-116-B100	KP2745-116R	KP2745-116R-B100
0.068-0.072 (1.7-1.8)	KP2745-072	KP2745-072-B100	KP2745-072R	KP2745-072R-B100
5/64 (2.0)	KP2745-564	KP2745-564-B100	KP2745-564R	KP2745-564R-B100

DIFFUSERS

Quantity	Product Number
1	KP4380-1
25	KP4380-1-B25

GUN TUBES

Description	Degree	Product Number
Water Cooled, 500A	45°	KP4526-45 ⁽¹⁾
Water Cooled, 500A	60°	KP4526-60 ⁽¹⁾
Water Cooled, 400A	45°	KP4527-45 ⁽²⁾
Water Cooled, 400A	60°	KP4527-45 ⁽²⁾

⁽¹⁾For use with Magnum PRO Water-Cooled 500A Gun only. ⁽²⁾For use with MagnumPRO Water-Cooled 400A Gun only.

NOZZLES

Nozzle Type	Quantity	5/8 in. ID	1/2 in. ID	3/4 in. ID
1/8 in. Recess	1	KP4523-1-62R	KP4523-1-50R	KP4523-1-75R
	25	KP4523-1-62R-B25	KP4523-1-50R-B25	KP4523-1-75R-B25
Flush	1	KP4523-1-62F	KP4523-1-50F	KP4523-1-75F
	25	KP4523-1-62F-B25	KP4523-1-50F-B25	KP4523-1-75F-B25
1/8 in. Stickout	1	KP4523-1-62S	KP4523-1-50S	KP4523-1-75S
	25	KP2743-1-62S-B25	KP4523-1-50S-B25	KP4523-1-75S-B25

NOTE: More nozzle sizes available at www.lincolnelectric.com

LINERS, 15 FT.

Wire Diameter, in. (mm)	Product Number
0.035-0.045 (0.9-1.2)	KP44-3545-15
.052-1/16 (1.3-1.6)	KP44-116-15
1/16-5/64 (1.6-2.0)	KP44-564-15

GUN CONNECTOR KITS

Manufacturer	Wire Feeder Model	Product Number
Lincoln Electric®	LN-7™ Series, LN-8™, LN-9™, LN-25® (up to .052 in./1.4 mm wire), LN-23P™	K466-1
	LN-8, LN-9 Series, LN-25 (1/16 in./1.6 mm and larger), LN-23P	K466-8
	LF-72™, LF-74™ Series, Flex Feed® 74 HT, Flex Feed 84, LN-25 PRO, LN-25X™, Activ8®, Activ8X™	K466-10
	Power Feed® 10, 10M, 25M, and 84	K466-10
Tweco® Adapted	No. 2, No. 3, No. 4 Guns	K466-2
Miller®	Intellimatic®, Sidekick, D-51A, Porto-MIG™ Millermatic® 130, 200, MM-35, S-42GL, S-52A, Swing Arc-Dual, Swing Arc-Single™, S-32S, 52D, 54D, 54E, 60 Series	K466-3

* All K466 series connectors are interchangeable on the K4521-2-10-45 and K4522-2-10-45 guns. The K4521-2-FM-45 and K4522-2-FM-45 have fixed Fast-Mate™ back end connections.

RECOMMENDED ACCESSORIES

GENERAL OPTIONS



Cool-Arc® 40 Water Cooler

A reliable water cooler available in both 115 and 230 volt models, it is compatible with all Lincoln water-cooled systems. Features an industry standard rugged industrial pump.

Order K1813-1 for 115/1/50/60
Order K2187-1 for 220-240/1/50/60



Cool Arc 55 Water Cooler

Designed to integrate with Power Wave S350 and S500 power sources to cool water-cooled welding guns or torches rated up to 500 amps. 115V/1/60.

Order K3086-1



Cool Arc 55S Water Cooler

The 55S model includes an ArcLink® communication flow sensor that detects water flow to prohibit welding when no flow is present.

Order K3086-2



Shown:
25 ft. (7.6 m) Hose

Water Hose Kit

Hose used to connect the Magnum PRO Water-Cooled Gun to a Cool Arc 55.

Order K4544-7 for 7 ft. (2.1 m) Hose
K4544-25 for 25 ft. (7.6 m) Hose



Quick Connect Water Adapter

Use with the K4544-7 or K4544-25 to connect the Magnum PRO Water-Cooled Gun to the Cool-Arc 40.

Order KP1529-1

PRODUCT SPECIFICATIONS

Product Name	Product Number	Amperage Rating (with Mixed Gas)	Wire Size Range in (mm)	Back End Connector	Cable Length ft. (m)	Net Wt. lbs (kg)
Magnum PRO Water-Cooled Guns	400A Gun	400A @ 100%	.035-5/64 (0.9-2.0)	K466-10	15 (4.5)	7.2 (3.2)
				Fast-Mate		
500A Gun	K4522-2-10-45	500A @ 100%		K466-10		7.4 (3.4)
				Fast-Mate		

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company® is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.

For best welding results with Lincoln Electric equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more detail.

All trademarks and registered trademarks are the property of their respective owners.

The Lincoln Electric Company
22801 St. Clair Avenue · Cleveland, OH · 44117-1199 · U.S.A.

www.lincolnelectric.com