High Performance Tig Welding Series



SPEED BUMP[™] HANDLE Fits the welder's hand like a fine instrument. Can rotate 360°. Retaining ring keeps cable cover secure.



DUAL BACK CAP SEAL Provides positive gas seal and protection against "HF" current leakage.



SPEED NUT[™] HOSE CONNECTIONS No more troublesome wire clamps. No tools or special hoses. Quick, easy repairs.



SW-320SA

HIGH PERFORMANCE CABLE ASSEMBLIES Soft, flexible over braided hoses and power cable provides maximum maneuverability. Larger copper conductor.

Speedway[®] Series sets a new track record.

Revolutionary

new design

packed with

performance

meet today's

TIG welding

features to

professional's sw-450 needs. sw-320



The new **Speedway**[®] **Series** torches bring together the best in design, materials and workmanship to give today's professional TIG welder the features to achieve unprecedented performance.

Features such as silver brazed copper construction which increases electrical current capacity and dissipates heat most efficiently.

Resilient high temperature silicone rubber insulation with high dielectric properties which resist "HF" current leakage, chipping, cracking and withstands temperatures to 500° F. Modern flexible over braided rubber hoses and power cables provide flexibility and maneuverability not available with traditional vinyl tube materials. Larger copper conductors that have greater current carrying capacity.

Speed Nut[™] hose connections mean no more troublesome wire clamps. No tools or special hose assemblies required.

The new **Speed Bump**[™] ergonomic handle shape lays comfortably in the hand. The handle can be rotated 360° for the optimum position to allow for long work cycles without tiring. The built-in retaining ring keeps the cable cover securely in place.

The **Speed Angle**[™] off-set torch body allows the welder access to difficult weld locations yet remains comfortable to hold.

Quality construction, modern design and premium materials while retaining the use of industry standard parts, such as collets, collet bodies, gas lenses, back caps and nozzles.

This interchangeability keeps costs low and accessories readily available to keep these torches working for years to come.

Quality, Performance and... Made in America.

ORDERING INFORMATION

SW-320 Deluxe Torch Package										
SW-320-12 DX	12 ¹ /2 ft. Torch Pkg									
SW-320-25 DX	25 ft. Torch Pkg									

SW-320SA Deluxe Torch Package

 SW-320SA-12DX
 12¹/2 ft. Torch Pkg

 SW-320SA-25DX
 25 ft. Torch Pkg

Deluxe Torch Package Includes:

Torch body, handle, over braided rubber hoses and power cable assembly, premium leather cable cover, 3/32" collet and collet body, #6 alumina nozzle, 3/32" x 7" tungsten electrode, short, medium and long back caps.

SW-450 Deluxe Torch Package

 SW-450-12 DX
 12¹/2 ft. Torch Pkg

 SW-450-25 DX
 25 ft. Torch Pkg

Deluxe Torch Package Includes:

Torch body, handle, over braided rubber hoses and power cable assembly, premium leather cable cover, 1/8" collet and collet body, #8 alumina nozzle, 1/8" x 7" tungsten electrode, short and long back caps.

OPTIONAL ACCESSORY KITS

AK-320 Deluxe Accessory Kit

 For SW-320 Model.
 Contains 1 Each.

 Collets:
 1/16", 3/32", 1/8"

 Collet Bodies:
 1/16", 3/32", 1/8"

 Gas Lenses:
 1/16", 3/32", 1/8"

 Aluminia Nozzles:
 #5, #6, #7

 Alum. Gas Lens Nozzles:
 #6, #7

 Tungsten Electrodes:
 1/16", 3/32", 1/8" x 7"

AK-450 Deluxe Accessory Kit

 For SW-450 Model.
 Contains 1 Each.

 Collets:
 3/32", 1/8", 5/32"

 Collet Body:
 universal

 Gas Lenses:
 3/32", 1/8", 5/32"

 Gas Lens Insulator
 Aluminia Nozzles:

 Alum. Gas Lens Nozzles:
 #6, #7, #8

 Alum. Gas Lens Nozzles:
 3/32", 1/8", 5/32" x 7"

SPECIFICATIONS

Maximum Amperage Capacity (ac-dcsp) Weight (Torch Body and Handle) Tungsten Size Capacity Maximum Tungsten Length Cooling Requirements Recommended Coolant Pressure

SW-320

320 AMPS 3.0 oz (84 gm) .020" - 5/32" (0.5 - 4,0mm) 7" (178mm) 1 QT./min (.946 L/min) 50 psi (345 Kpa)

For more information contact your local welding supply distributor.

SW-320SA 320 AMPS 3.0 oz (84 gm) .020" - 5/32" (0.5 - 4,0mm) 7" (178mm) 1 QT./min (.946 L/min) 50 psi (345 Kpa)


SW-450

450 AMPS 11 oz (312 gm) .040" - 3/16" (1,0 - 4,8mm) 7" (178mm) 1.75 QT./min (1.66 L/min) 50 psi (345 Kpa)



TEC Welding Products, Inc. P.O. Box 1870, San Marcos, CA 92079 USA (760) 747-3700 • Fax (760) 747-2121 www.tectorch.com

© Copyright 2001-2013 TEC WELDING PRODUCTS



COLLETS • COLLET BODIES • GAS LENS

GAS NOZZLES

ITEM	Electrode Diameter	.040 1,0	1/16 1,6	3/32 2,4	1/8 3,2	5/32 4,0	3/16 4,8	ITEM	NO. SIZE	4 1/4"	5 5/16"	6 3/8"	7 7/16"	8 1/2"	10 5/8"	11 11/16"	12 3/4"
Α	COLLET	10N22HD	10N23HD	10N24HD	10N25HD	54N20HD	18C36	E	ALUMINA	54N18	54N17	54N16	54N15	54N14		54N19	
В	COLLET BODY	NCB-36											54N15HPS	54N14HPS			
С	GAS LENS	18GL04	18GL16	18GL32	18GL18	18GL53	18GL36	F	LONG ALUMINA 3"		54N17L	54N16L	54N15L				
D	LG. DIA GAS LENS	45V94	45V95	45V96	45V97	45V98	45V99	G	ALUMINA LG. DIA. GAS LENS			57N75		57N74	53N88		53N87**
								н	METAL						57N78		57N77

* Nozzles Available In HPS High Performance Series (Gray Color).

** #15 53N89 15/16" ID X 1 7/8" Long.